

## Double Direction Thrust Ball Bearings With Sphered Housing Washers

select	Inquiry Code	Seat washer	Principal Dimensions (Size)			Basic Load Rating kN		Fatigue load limit kN	Speed ratings r/min		Weight (kg)
			d (mm)	D (mm)	H1 (mm)	Dynamic C	Static C0		Reference	Limiting speed	
54306	U306	25	60	46	35.8	65.5	2.4	2800	3800	0.58	
54207	U207	30	62	42	35.1	73.5	2.7	2800	4000	0.53	
54208	U208	30	68	44	44.2	96.5	3.6	2800	3800	0.63	
54307	U307	30	68	52	49.4	96.5	3.55	2400	3400	0.85	
54308	U308	30	78	59	61.8	122	4.5	2200	3000	1.15	
54209	U209	35	73	45	39	86.5	3.2	2600	3600	0.78	
54309	U309	35	85	62	76.1	153	5.6	1900	2800	1.6	
54409	U409	35	100	86	124	240	9	1500	2000	3	
54310	U310	40	95	70	81.9	170	6.3	1700	2400	2.3	
54410	U410	40	110	92	148	305	11.4	1400	4900	4.45	
54211	U211	45	90	55	58.5	134	4.9	2200	3000	1.3	
54312	U312	50	110	78	101	224	8.3	1500	2200	2.9	
54316	U316	65	140	95	159	390	13.7	1300	1800	5.55	
54416M	U416	65	170	140	307	750	25	850	1200	17.5	
54317	U317	70	150	105	174	405	14	1100	1500	7.95	
54420M	U420	80	210	176	371	1060	31.5	700	950	29	